VBOX-3620-M12X

Intel Gen6 Core i7-6600U CPU with Isolated Input 3×6 and 1×6 iAMT

In-Vehicle Computer











Wide Range



Wireless





Taiwan Patent No. M447854 Taiwan Patent No. M448011

System

Oystelli	
CPU	Intel Gen6 Core i7-6600U 2.6GHz up to 3.4GHz
	Intel Gen6 Core i5-6300U 2.4GHz up to 3GHz
	Intel Gen6 Core i3-6100U 2.3GHz
	Intel Gen 6 Dual Core 3955U 2.0GHz
Memory	2 x SO-DIMM DDR4 up to 32GB
LAN Chipset	2 x Intel I210AT and 1 x Intel i219LM
Audio	Realtek ALC662 HD Codec Onboard
Watchdog	Watchdog Timer Support, Offer 1 – 255 Step

I/O	
Serial Port	4 x RS-232/422/485, w/ isolation (Auto Direction Control)
USB Port	2 x USB 3.0 Ports, 2 x USB 2.0 Ports
LAN	3 x 10/100/1000 Mb/s w/ M12 x-code (1 port with iAMT)
Video Port	2 x DP Port, 1 x VGA (Support Triple Independent Display)
DIO Port	8 x GPI and 4 x GPO w/ isolation
Audio	1 x Line-out and 1 x Mic-in (Line-in Optional)
SIM Card Socket	2 x SIM Card Sockets, supported onboard with eject
	6 x SIM Card Sockets (Optional)
Expansion Bus	3 x Mini-card slots
	1 x M.2 slot

Graphics

0. up00	
Graphics	Intel® HD Graphics 520
	DirectX Video Acceleration (DXVA) for Accelerating Video
	Processing - Full AVC/VC1/MPEG2 HW Decode
	Supports DirectX 11/10.1/10/9 and OpenGL 4.0
Resolution	Up to 4096 x 2304@60 Hz

Storage

	0	
Type		2x2.5" Drive Bay for SATA Type HDD/SSD, RAID 0, 1, 5
		1 × CATA DOM

Features

- Intel Core i7-6600U / i5-6300U / i3-6100U
- Wireless support LTE, 3.5G w/ SIM Card, WLAN GPS Dead Reckoning, GSM/GPRS, BT
- 3 x GbE including 1 with iAMT
- Isolated wide Input Range 9-36VDC
- Smarter Vehicle Power Ignition for Variety Vehicle
- Dual Hot Swappable SATA Storage, RAID 0,1,5
- EN50155 Tx

Power Requirement

	Patent No. : M447854 - Build-in Battery
Battery (UPS)*	Internal Battery Kit for 10 Mins Operating (Optional)
Power Off Control	Power off Delay Time Setting by Software and BIOS
Power Managemen	t Vehicle Power Ignition for Variety Vehicle
Power Protection	Automatics Recovery Short Circuit Protection
Power Input	9V - 36V DC Power Input with Isolation

* with 6 x SIM card slots option cannot have Battery option

Environmental

Operating Temp.	-40°C ~ 70°C
Storage Temp.	-40°C ~ 80°C
Relative Humidity	0% RH – 95% RH
Vibration(random)	2.5g@5~500 Hz with SSD
Vibration Operating	MIL-STD-810G, Method 514.5, Category 20,
	Ground Vehicle-Highway
Truck Storage	MIL-STD-810G, Method 514.5, Category 24, Integrity Test
Shock	Operating: MIL-STD-810G, Method 516.5, Procedure I,
	Trucks and semi-trailers=15G (11ms) with SSD
Crash Hazard	MIL-STD-810G, Method 514.6 C-1, Procedure V,
	Ground equipment=100g
Certifications	CE, FCC Class A, EN50155, EN50121

Mechanical

Construction	Aluminum Alloy
Mounting	Supports Both of Wall-mount/VESA-mount
Weight	1900g
Dimensions	250 x 150 x 55 mm

Ordering Information

Part Number	VBOX-3620-M12X-000
Description	Intel Gen6 Core i7-6600U CPU with Isolated Input
	3x GbE with 1 x iAMT In-Vehicle Computer